

Range: **MOTO AGM DRY**

Type name: **YTX12-BS**



| PERFORMANCES*     |                | CONFIGURATION |                        |
|-------------------|----------------|---------------|------------------------|
| Voltage:          | 12 V           | Size:         | 150x87x130 mm (Moto)   |
| Capacity:         | 10 Ah (10h)    | Polarity:     | 1                      |
| C. Cranking (EN): | 180 A          | Terminal:     | C (squared)            |
| Vibration (EN):   | Not applicable | Holddown:     | -                      |
| Duration (EN):    | Not applicable | Ventilation:  | Vent with valve (VRLA) |
| Self-Discharge:   | Not applicable | Maintenance:  | Not required (MF)      |

\*According to standard EN 50342

| INTERNAL CONSTRUCTION |                      | COMPONENTS      |                    |
|-----------------------|----------------------|-----------------|--------------------|
| Tecnology:            | Dry charged AGM      | Box/Recipiente: | PP/black           |
| Alloy:                | Calcium              | Lid:            | PP/black           |
| Separator:            | AGM (glass mat)      | Plugs:          | Pressure, PP/black |
| Total Weight:         | 3,17 kg              | Handles:        | -                  |
| Acid:                 | Side-bottle included |                 |                    |
| Origin:               | Asia                 |                 |                    |

| RECOMMENDATIONS |  |
|-----------------|--|
| Storage:        | Ensure proper stock rotation. Avoid moisture.        |
| Recharge:       | Not required, but convenient after first activation. |
| Installation:   | Never install in tilted or horizontal position.      |