

Range: **MONOBLOCK**

Type name: **OZX250.A**



		
3	-	1

PERFORMANCES*		CONFIGURATION	
Voltage:	12 V	Size:	518x273x240 mm (C)
Capacity:	250 Ah (100h)	Polarity:	3
Cap. 10/20h:	220/230 Ah	Terminal:	1 (taper)
Energy at 100h:	3 kWh	Holddown:	-
Cicles at 50%:	100	Ventilation:	Individual plugs
PV Cicles (24%):	500	Maintenance:	Very low maintenance
Self-Discharge:	12 months		
<small>(from the date of production, at 25°C)</small>			

\*According to standards IEC 60896/61427

INTERNAL CONSTRUCTION		COMPONENTS	
Technology:	Punched, with regular surface	Container:	PP/white
Alloy:	Calcium	Lid:	Flat, PP/white
Separator:	PE envelope	Plugs:	Screw, PP/white
Total Weight:	54,6 kg	Handles:	On container, rope/black
Origin:	Europe		

RECOMENDATIONS	
Storage:	Check voltage every 6 months. Avoid exposure to sub-zero temperatures.
Recharge:	Use automatic chargers with constant voltage.
Installation:	Use the appropriate cable section and length. Keep connections tight.

### TABLES & CHARTS

### MONOBLOCK

### OZX250.A

**OZX250.A BATTERY DISCHARGE PERFORMANCE AT 25°C**

Discharge rate	C5 (5h)	C5 (5h)	C20 (20h)	C100 (100h)
End of discharge voltage	10,20 V	10,50 V	10,50 V	10,80 V
Discharge capacity	210 Ah	230 Ah	240 Ah	250 Ah

