## **Motorcycle Batteries**



## intAct Bike-Power GEL

Sealed maintenance-free GEL battery | electrolyte immobilized by gel-additive | wet charged













## FOR HEAVY LOADS, INCLUDING ABS

Delivers 30% more starting power for modern motorcycles with many electrical consumers and covers consumption peaks. Low self-discharge, bike starts reliably even after up to 3 months. Our recommendation if many consumers are installed or the motorcycle is rarely used.

- Even more cycle-resistant than Bike-Power AGM and Bike-Power SLA of the same box size.
- » Low self-discharge. For seasonal use.
- Very high vibration-resistance. Electrolyte immobilized by geladditive.
- 30% more starting power than a conventional battery of the same box size. For motorcycles with many consumers, including ABS.
- Sealed maintenance-free battery. Refilling is neither possible nor necessary.
- » Wet charged. Ready to use.

## Datasheet

Base plate





Artnum.	IG YT7B-4
Japan-Code	CT7B-4, GT7B-4
Volt	12V
Capacity	6 AH (c20)
CCR -18°C (EN)	120 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 kg/l (25°)
Size (LxWxH)	150 x 65 x 94 mm
Weight	2,4 kg
Pos. of Terminal	1
Technology	Sealed maintenance-free GEL battery   electrolyte immobilized by gel-additive   wet charged
Terminal	FRONT



